


CONEXÕES SAE - JIC (ISO 8434-2 / SAE J514)

UNIÃO (Union)

070101



Ref.	Tubo 1 O.D.	Rosca UNF	Tubo 2 O.D.	Rosca UNF	Ex	L	D	D1
070101-4-4 C	1/4	7/16-20	1/4	7/16-20	1/2	35	4	4
070101-5-4 C	5/16	1/2-20	1/4	7/16-20	9/16	35	6	5
070101-5-5 C	5/16	1/2-20	5/16	1/2-20	9/16	35	6	6
070101-6-4 C	3/8	9/16-18	1/4	7/16-20	5/8	36	8	4
070101-6-5 C	3/8	9/16-18	5/16	1/2-20	5/8	36	8	6
070101-6-6 C	3/8	9/16-18	3/8	9/16-18	5/8	36	8	8
070101-8-4 C	1/2	3/4-16	1/4	7/16-20	13/16	39	10	5
070101-8-6 C	1/2	3/4-16	3/8	9/16-18	13/16	39	10	8
070101-8-8 C	1/2	3/4-16	1/2	3/4-16	13/16	41	10	10
070101-10-6 C	5/8	7/8-14	3/8	9/16-18	15/16	43	12	8
070101-10-8 C	5/8	7/8-14	1/2	3/4-16	15/16	45	12	10
070101-10-10 C	5/8	7/8-14	5/8	7/8-14	15/16	48	12	12
070101-12-8 C	3/4	1.1/16-12	1/2	3/4-16	1.1/8	50	16	10
070101-12-10 C	3/4	1.1/16-12	5/8	7/8-14	1.1/8	52	16	12
070101-12-12 C	3/4	1.1/16-12	3/4	1.1/16-12	1.1/8	55	16	16
070101-14-14 C	7/8	1.3/16-12	7/8	1.3/16-12	1.1/4	56	18	18
070101-16-12 C	1	1.5/16-12	3/4	1.1/16-12	1.3/8	56	22	16
070101-16-16 C	1	1.5/16-12	1	1.5/16-12	1.3/8	57	22	22
070101-20-16 C	1.1/4	1.5/8-12	1	1.5/16-12	1.11/16	61	28	22
070101-20-20 C	1.1/4	1.5/8-12	1.1/4	1.5/8-12	1.11/16	62	28	28
070101-24-24 C	1.1/2	1.7/8-12	1.1/2	1.7/8-12	2	70	33	33
070101-32-32 C	2	2.1/2-12	2	2.1/2-12	2.5/8	87	45	45

Conexões com ref. em Aço Carbono (C)

1 - Materiais das Conexões: **Aço Inoxidável (S) = 070101-8-8 S**
Latão (B) = 070101-8-8 B

2 - Consulte para outras combinações de lado JIC.

3 - Pressão de trabalho aplicada para aço carbono (C) e aço inoxidável (S)
Vide informações técnicas - Pág. 2

4 - Pressão de trabalho aplicada em latão, sob consulta.