


ADAPTADORES - SAE J514

CURVA FÊMEA / MACHO NPT (Male Female Thread 45° Elbow)

140339.....




Ref.	Rosca A NPT	Rosca B NPT	N 3	N 4
140339-2-2 C	1/8	1/8	12	18
140339-4-4 C	1/4	1/4	16	26
140339-6-6 C	3/8	3/8	18	26
140339-8-8 C	1/2	1/2	23	34
140339-12-12 C	3/4	3/4	25	35
140339-16-16 C	1	1	29	44
140339-20-20 C	1.1/4	1.1/4	41	46
140339-24-24 C	1.1/2	1.1/2	43	52
140339-32-32 C	2	2	56	55

Adaptador com ref. em Aço Carbono (C)

TE FÊMEA / MACHO NPT (Male Female Thread Tee)

140424.....




Ref.	Rosca A NPT	Rosca B NPT	N	N 1
140424-2-2-2 C	1/8	1/8	20	17
140424-4-4-4 C	1/4	1/4	28	22
140424-6-6-6 C	3/8	3/8	31	26
140424-8-8-8 C	1/2	1/2	37	31
140424-12-12-12 C	3/4	3/4	40	35
140424-16-16-16 C	1	1	50	41
140424-20-20-20 C	1.1/4	1.1/4	60	43
140424-24-24-24 C	1.1/2	1.1/2	67	53
140424-32-32-32 C	2	2	76	61

Adaptador com ref. em Aço Carbono (C)

TE FÊMEA / MACHO NPT (Male Female Thread Tee)

140425.....



Ref.	Rosca A NPT	Rosca B NPT	N	N 1
140425-2-2-2 C	1/8	1/8	20	17
140425-4-4-4 C	1/4	1/4	28	22
140425-6-6-6 C	3/8	3/8	31	26
140425-8-8-8 C	1/2	1/2	37	31
140425-12-12-12 C	3/4	3/4	40	35
140425-16-16-16 C	1	1	50	41
140425-20-20-20 C	1.1/4	1.1/4	60	43
140425-24-24-24 C	1.1/2	1.1/2	67	53
140425-32-32-32 C	2	2	76	61

Adaptador com ref. em Aço Carbono (C)

1 - Materiais dos Adaptadores: **Aço Inoxidável (S) = 140339-8-8 S**
140424-8-8-8 S
140425-8-8-8 S

2 - Consulte para outras combinações de Rosca NPT.