


CONEXÕES SAE - JIC (ISO 8434-2 / SAE J514)

União Macho NPT (ANSI/ASME B 1.20.1) (Male Stud Connector)

070102



Ref.	Tubo	Rosca A UNF	Rosca B NPT	L	Ex
070102-4-2 C	1/4	7/16-20	1/8	31	1/2
070102-4-4 C	1/4	7/16-20	1/4	36	9/16
070102-4-8 C	1/4	7/16-20	1/2	43	7/8
070102-5-2 C	5/16	1/2-20	1/8	31	9/16
070102-5-4 C	5/16	1/2-20	1/4	36	9/16
070102-6-2 C	3/8	9/16-18	1/8	32	5/8
070102-6-4 C	3/8	9/16-18	1/4	36	5/8
070102-6-6 C	3/8	9/16-18	3/8	36	3/4
070102-6-8 C	3/8	9/16-18	1/2	43	7/8
070102-8-4 C	1/2	3/4-16	1/4	39	13/16
070102-8-6 C	1/2	3/4-16	3/8	39	13/16
070102-8-8 C	1/2	3/4-16	1/2	46	7/8
070102-8-12 C	1/2	3/4-16	3/4	47	1.1/8
070102-10-6 C	5/8	7/8-14	3/8	43	15/16
070102-10-8 C	5/8	7/8-14	1/2	48	15/16
070102-10-12 C	5/8	7/8-14	3/4	50	1.1/8
070102-12-8 C	3/4	1.1/16-12	1/2	52	1.1/8
070102-12-12 C	3/4	1.1/16-12	3/4	53	1.1/8
070102-12-16 C	3/4	1.1/16-12	1	58	1.3/8
070102-14-12 C	7/8	1.3/16-12	3/4	53	1.1/4
070102-16-12 C	1	1.5/16-12	3/4	54	1.3/8
070102-16-16 C	1	1.5/16-12	1	58	1.3/4
070102-20-16 C	1.1/4	1.5/8-12	1	61	1.11/16
070102-20-20 C	1.1/4	1.5/8-12	1.1/4	62	1.11/16
070102-24-20 C	1.1/2	1.7/8-12	1.1/4	67	2
070102-24-24 C	1.1/2	1.7/8-12	1.1/2	68	2
070102-32-32 C	2	2.1/2-12	2	79	2.5/8

Conexões com ref. em Aço Carbono (C)

1 - Materiais das Conexões: **Aço Inoxidável (S) = 070102-8-8 S**
Latão (B) = 070102-8-8 B

2 - Consulte para outras combinações de lado JIC - Rosca NPT.

3 - Pressão de trabalho aplicada para aço carbono (C) e aço inoxidável (S)
Vide informações técnicas - Pág. 2

4 - Pressão de trabalho aplicada em latão, sob consulta